

## PRODUCT SPECIFICATION



- 1. PRODUCT CODE**      **AWC24103**
- 2. DESCRIPTION**      2 Core Flat Twin Sheath 36/.32 (2.89mmsq).  
Oxygen Free Plain Copper Wire.  
Non Migratory V-90 PVC Insulated.  
Non Migratory 5V-90 PVC Sheathed Automotive cable.  
RoHS compliant P.V.C.  
Extra Low Voltage Not for Mains connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:**      36 strands of 0.32 mm nom. Annealed Copper to AS/NZS1125  
drawn from Class 110A copper to AS/NZS1574.
- Max. D.C. resistance at 20C:      6.4 ohms / km
- 3.2 INSULATION:**      Coloured Non Migratory V-90 P.V.C. to AS/NZS3808.
- Nominal Diameter:      3.0 mm  
Nominal Wall Thickness:      0.4 mm
- 3.3 CORE COLOURS:**      1. Red  
2. Black  
Laid parallel
- 3.4 SHEATH:**      Coloured Non Migratory P.V.C. type 5-V90 to AS/NZS3808.  
Flat configuration
- Nominal Diameter:      4.50 x 7.40 mm  
Nominal Wall Thickness:      0.7 mm